ADDMASTER
IJ6080

Small Receipt/Validation Printer

Transaction Printing...
3 models to choose from

FEATURES INCLUDE:

- Fast, Quiet, Reliable
- Outstanding output on plain and recycled paper
- 3-inch wide (76 mm) roll paper with auto load
- Easy-drop validation slot for checks and forms
- Optional Epson or TPG/Axiohm emulations
- Low power consumption
- Operates with 24V power supply

3 MODELS:

- Receipt
- Validation
- Receipt/validation

The IJ6080 prints high quality receipts with remarkable efficiency. With its compact footprint, the IJ6080 easily fits on any teller counter. A modern, ergonomic design optimizes form handling, and interfacing is made easy with available software drivers and Epson or TPG/Axiohm emulations. Addmaster is the acknowledged leader in inkjet transaction printers, with 150,000 printers installed at banks worldwide.

- Small footprint
- Quiet
- Compact
- User-friendly
- Trouble free

Benchmark is an Authorized Service Center
for **ADDMASTER** Products

Powered by: **Benchmark**
TECHNOLOGY GROUP

Print Method:

Thermal Inkjet Cartridge HP C6602A

Print Characteristics:

Resolution: 96 x 144 dpi

Character Height: 0.125"

Graphics Capability: Logos, bar codes

Receipt Characteristics:

Paper Roll Width: 3" (76 mm)

Characters Per Line: 32-42 (font dependent)

Line Spacing: 5.5 lines per inch

Print Speed:

Characters Per Second (Peak): 375

Line Feed: 5.0" per second

Throughput*: 1.2" per second

Interface:

Serial RS232

Baud Rate:

9,600, 19,200, 38,400

Microprocessor:

Intel 80C251

Memory:

Code (downloadable): 128K x 8

Flash Data: 32K x 8 RAM

Code Emulation:

Epson ESC/POS

TPG

Dimensions:

Width: 6.5"

Depth: 6" (9" with Paper Roll Attachment)

Height: 3.4"

Power Source:

24V@600ma (external)

Power Consumption:

Operating: 12 watts

Standby: 12 watts

Operating Environment:

10 to 40 degrees C

10 to 90 percent RH (non-condensing)

Options:

Validation

Multi-purpose interface for

- Cash Drawer

- 2nd Serial Port

Validation Characteristics:

Vertical Print Field: 2.8"

Top Line: 1.5" from bottom of form

Line Spacing: 6.6 lines/in.

Number of Lines: 8 (Model 6080) 1 (Model 6010)

* Throughput is time to print benchmark 6"
   receipt. Actual speed may vary based on print
   requirements.