



SmartSource®

ReceiptNOW®



SmartSource
ReceiptNOW Elite



SmartSource
ReceiptNOW

Our Customers Say it Best!

“Integrating the ReceiptNOW printers and SmartSource scanners enabled us to deliver an enhanced client experience while capitalizing on processing efficiencies.” – Rachel Emery, AVP Office Automation Manager, United Bank & Trust

SmartSource ReceiptNOW

Prints receipts right at your check scanner. Engineered to fit under Digital Check SmartSource scanners – combining scanner and receipt printer units into one footprint, saving valuable counter space!

SmartSource ReceiptNOW — Designed to fit under the SmartSource Professional, Value, Expert, Adaptive, and other scanners.

SmartSource ReceiptNOW Elite — Engineered to fit beneath the SmartSource Elite series scanners.

Features

- Quiet thermal receipt printer
- Frees up teller space
- Simple pull-out, drop-in paper
- Largest paper roll
- Full or partial paper cut

- Fast 8 inches/second (20 cm/second) delivery
- Less maintenance than matrix printers
- Fast installation for existing sites
- Three year warranty (advanced exchange available)

Compatibility

- USB or Ethernet interface
- Full 108 std & international fonts w/barcode
- Prints on standard, security, non-BPA and 2-color paper
- International power compliant
- Worldwide certifications

Customizable Teller Receipt

- Top/bottom logos
- Border messages
- Watermarks
- Windows True Type fonts
- Color text/graphics – using 2-color paper



SmartSource ReceiptNOW Technical Information

Models

SRNELITE-USB – ReceiptNOW Elite, USB Interface
 SRNELITE-ETH – ReceiptNOW Elite, Ethernet Interface
 SRN2PTR-USB – ReceiptNOW, USB Interface
 SRN2PTR-ETH – ReceiptNOW, Ethernet Interface

Printing/Feed/Cut

Direct Thermal Printer
 Black and Two Color Capability
 Black Print Speed 8 inches/second (20 cm/second)
 Resolution: 203 x 180 dpi
 95 Alphanumeric, 13 International Characters w/Kanji
 True Type Fonts available when being driven as a Windows printer
 1D/2D Bar Code Fonts
 512K on-board Logo Flash
 Full/Partial Auto Cutter

Controls

On/Off Switch
 Paper Empty/Low LED's w/Audible Alerts
 Paper Feed Button
 Paper Width Adjustment
 Power indicator

Interface

USB
 Standard ESC/POS Command Set
 OPOS & JavaPOS, Auto Status Back (ASB)

Dimensions

	ReceiptNOW	ReceiptNOW Elite
Height:	5.4 inches (13.7 cm)	5.2 inches (13.2 cm)
Width:	6.1 inches (15.5 cm)	5.7 inches (14.5 cm)
Length:	15.3 inches (38.8 cm)	9.5 inches (24.2 cm)

Environment/Acoustics

5~50°C Operating Environment
 Acoustics < 60 dba Cutting or Printing



Power

International Power 100-240VAC, 50/60Hz
 Power Supply Included

Paper/Loading

Standard, Security, Non-BPA, 2-Color Paper
 2.4 in. to 3.25 in. (6.1 cm to 8.3 cm) Paper Widths - Adjustable
 Largest 3.25 in. (8.3 cm) Diameter Paper Roll
 Slide Out Tray, Drop-in Paper

Warranty/Service

3 Year Warranty
 Advanced Exchange Available

Graphic Receipt Customization

Multiple Graphics Can be Placed Anywhere
 Custom Messages
 Watermarks

Host OS

Win 2000, XP, Vista (32/64), Windows 7 (32/64), Windows 8 (32/64),
 Windows 10 (32/64)

Maintenance

Print Exerciser & Diagnostic Software
 Operator Guide

Certifications

FCC Class B, CE, VCCI, for EMI Emissions
 CE, for Susceptibility and ESD
 CE, CB, CUL/UL 60950, for Safety
 RoHS Compliant (EU)
 2010 Appliance Efficiency Regulations, California, Title 20

NOTES: Not every API Operating System combination may be qualified. Contact your application provider for more information. Specific capabilities may not be supported by every API or will require a minimum API version. Contact Digital Check for more information.

SmartSource and ReceiptNOW are registered trademarks of Digital Check Corp. Ranger is a registered trademark of Silver Bullet Technology, Inc. All other brands and products referenced in this document are acknowledged to be the trademarks or registered trademarks of their respective holders. Specifications are subject to change without notice.

3/17 All rights reserved. © 2017 Digital Check Corp.



SmartTIP For more information use your smartphone and snap a photo.