

# Vision neXt™

## Receipt Printer

	<b>Stand-alone</b>	<b>Stackable</b>
<b>Dimensions</b>	Height: 127 mm (5") Width: 137 mm (5.39") Length: 151 mm (5.94") Weight: 0.8 Kg (1.8 lbs)	Height: 141 mm (5.55") Width: 144 mm (5.67") Length: 235 mm (9.25") Weight: 2.4 Kg (5.3 lbs)
<b>Weight</b>	0.8 Kg (1.8 lbs).	
<b>Print Method</b>	Thermal line printing; monochrome.	
<b>Speed</b>	100 mm/sec; ~30 lps.	
<b>Resolution</b>	203 DPI.	
<b>Cutter</b>	Automatic, guillotine type, full or partial cut.	
<b>Paper Roll</b>	80 mm (width) x 60 mm (diameter).	
<b>Print Width</b>	72 mm.	
<b>Interface</b>	USB 2.0 Hi-Speed.	
<b>Software</b>	Microsoft Windows driver for XP, Vista, and Windows 7 & 8. OPOS driver (UPOS 1.13 compliant).	
<b>Certifications</b>	UL / FCC Class A / CE. Electronics and mechanics following European RoHS and WEEE Directives.	
<b>Power Supply</b>	Desktop Switching Supplier. Autosensing Input from 100 to 240 Vac, 50 to 60 Hz. Output: 24 Vdc, 2.7A (65W). Meets CEC level V.	

## HARDWARE OPTIONS

### Inset USB Hub

Plugs into the rear side of the scanner with no footprint increase.

3 USB ports – 1 exposed and 2 internal.

Pass-through channel for power cable.

### IR Capture

Infrared front image capture for security applications.



[www.panini.com](http://www.panini.com)